

Haley & Aldrich, Inc. One Arizona Center 400 E. Van Buren St., Suite 545 Phoenix, AZ 85004 602.760.2450

#### **TECHNICAL MEMORANDUM**

8 July 2015 File No.: 38681

**TO:** Rebecca Sawyer, Vice President - Sustainability

**Excelsior Mining Corporation** 

FROM: Pejman Eshraghi, P.E., Project Manager

Haley & Aldrich, Inc.

**SUBJECT:** Presence of Petroleum Hydrocarbons in Groundwater at Gunnison Copper Project

Located in Dragoon, Arizona

The purpose of this technical memorandum (tech memo) is to document the presence of dissolved petroleum hydrocarbons and petroleum free product (light non-aqueous phase liquid [LNAPL]) floating on top of groundwater at the referenced site (Figure 1).

#### **Free Product Recovery and Groundwater Monitoring**

In December 2014, Excelsior Mining Corporation (Excelsior) discovered that some of the existing core holes drilled onsite may be impacted by petroleum hydrocarbons. Excelsior cited detection of petroleum odor in groundwater and petroleum residue on monitoring equipment that was lowered into core holes CS-09, CS-10, CS-14, DC-09, and NSM-003.

On 26 January 2015, Haley & Aldrich provided Excelsior with a plan to conduct groundwater monitoring and, if necessary, a free product recovery test on the core holes. Subsequently, Haley & Aldrich mobilized to the site on 5 February and 11 February 2015 to implement the approved plan. On 5 February 2015, Haley & Aldrich measured the free product thickness in core holes CS-10 and CS-14 to be 1.47 and 1.93 feet, respectively (Table I). There was no measurable free product in core holes NSM-003, CS-09, and DC-09. However, a greasy substance was detected in CS-09 that appeared to be consistent with lubricant used for drilling operations.

On 11 February 2015, Haley & Aldrich removed 8 gallons of free product and oily water, using a bailer, from core holes CS-10 and CS-14. Haley & Aldrich estimates that approximately 1.25 gallons of the recovered liquid was free product, while the rest was oily water beneath the floating free product (Table I). The recovered liquid was dropped off at a recycling facility (Appendix A). Following recovery of free product, Haley & Aldrich continued periodic monitoring of the two core holes, through 26 February 2015, to monitor the return of free product. On 26 February 2015, the free product thickness in core hole CS-10 was measured to be approximately 0.25 feet, while no free product was measured in CS-14.

Following removal of the free product from core holes CS-10 and CS-14, Haley & Aldrich collected investigative (no purging) samples of the groundwater using a bailer to determine the concentrations of dissolved volatile organic compounds (VOCs) and polynuclear aromatic hydrocarbons (PAHs). Haley & Aldrich also collected an investigative sample of groundwater from core hole NSM-003, but was unable to collect a sample from core hole CS-09 as the bailer became fouled by the greasy substance in the core hole. Haley & Aldrich did not collect a sample from DC-09, because the well had been purged using air lifting, and collection of a representative water sample was not possible due to development activities. The three groundwater samples were analyzed for VOCs and PAHs using U.S. Environmental Protection Agency (USEPA) Test Methods 8260B and 8310, respectively.

The water samples from the wells containing free product (CS-10 and CS-14) contained elevated concentrations of benzene, toluene, ethylbenzene, and xylenes (BTEX). However, only benzene concentrations exceeded its Arizona Aquifer Water Quality Standard (AWQS) of 5 micrograms per liter ( $\mu$ g/L) with concentrations of 7.3 and 310  $\mu$ g/L in CS-10 and CS-14, respectively. The water samples also contained other volatile hydrocarbons and PAHs. Table II presents a summary of the detected petroleum hydrocarbons in the groundwater samples collected from CS-10 and CS-14. Table III provides the chemical categories with which each detected compound is associated.

Recognizing that the fuels detected at the site are highly degraded, Haley & Aldrich performed a series of ratio calculations with BTEX, which represents the most volatile aromatic hydrocarbons. The calculated ratios (Table IV) are compared to the published values<sup>1</sup> of gasoline residues in groundwater. The elevated concentrations of BTEX and the results of the comparison suggest that the detected concentrations of BTEX in the groundwater samples collected from CS-10 and CS-14 are consistent with degraded gasoline or a mixture of petroleum products including gasoline.

The groundwater sample collected from NSM-003 contained detectable concentrations of tert-butyl alcohol (TBA), a gasoline additive that is added to gasoline as an oxygenate and an engine anti-knock compound. TBA is more soluble in groundwater than BTEX, tends to partition from the vapor phase and dissolves into groundwater, and is not significantly slowed by subsurface sorptive processes<sup>2</sup>. Therefore, its detection alone is not indicative of a release of pure TBA. Rather, it is a more reasonable scenario that TBA originally entered the environment as a constituent of the gasoline detected in groundwater in CS-10 and CS-14.

Since the original groundwater sampling, VOCs and PAHs have been detected in groundwater samples collected from new core holes (NSH-007, NSH-009, NSH-015, and NSH-22), which were drilled under the oversight of Haley & Aldrich. The detected concentrations are summarized in Table II. Of particular interest were the detection of 1,2-dichloroethane (1,2-DCA) at concentrations of 0.96 and 0.36  $\mu$ g/L in groundwater samples collected from NSH-15 and NSH-22, respectively; and the detection of the highest toluene concentration of 2,080  $\mu$ g/L in the groundwater sample collected from NSH-22. The compound 1,2-DCA is a lead scavenger and is specifically added to leaded gasoline as an additive to prevent build-up of lead oxide deposits inside internal combustion engines. The presence of 1,2-DCA in groundwater along with other VOCs and PAHs, although in low concentrations below AWQS, is further evidence that groundwater impact is likely due to a gasoline release.

<sup>&</sup>lt;sup>2</sup> ITRC, February 2005. Overview of Groundwater Remediation Technologies for MTBE and TBA.



<sup>&</sup>lt;sup>1</sup> Kaplan, I. R., Galperin, Y., Lu, S-T. & Lee, R-P., 1997. "Forensic Environmental Geochemistry: Differentiation of Fuel Types, Their Sources and Release Time". *Organic Geochemistry* 27:289–317. Table 8.

Excelsior Mining Corporation 8 July 2015 Page 3 of 4

The toluene concentration of 2,080  $\mu$ g/L in NSH-022 exceeds its established AWQS of 1,000  $\mu$ g/L. Toluene is used as a solvent, used to manufacture benzene, and added to gasoline to improve its octane rating. Similar to TBA, detection of toluene in NSH-22 alone does not indicate a pure toluene release. Rather, it is a more reasonable scenario that toluene entered the environment as a constituent of gasoline.

#### Source(s) of Contamination

At this time, the source(s) of the gasoline impact and or the location(s) where the impact may have occurred are unknown. Haley & Aldrich reviewed the Arizona Department of Environmental Quality's (ADEQ's) readily available Leaking Underground Storage Tank (LUST) public record and identified The Thing Dairy Queen Travel Center (The Thing; Facility ID 0-000748 | LUST ID 4387) as a potential off-site source. On 27 March 1996, this facility permanently closed (via removal) three gasoline USTs. Soil samples collected beneath the USTs at 12 feet below ground surface (bgs) were tested for BTEX. The maximum concentrations of BTEX detected in the soil samples collected from the tank pit were 21, 500, 170, and 850 milligrams per kilogram (mg/kg), respectively. Soil that was removed during tank removal was placed in the tank pit<sup>3</sup>. Bedrock was reportedly observed at less than 2 feet below the tanks. The ADEQ's UST Programs unit opened three LUST case files and requested the facility to begin site characterization.

On 7 February 2000, the facility conducted site characterization of the shallow soils by installation of six soil borings to total depths ranging from 2 to 10 feet bgs, the depth at which bedrock was encountered. The concentrations of BTEX compounds were mostly below the laboratory's minimum reporting limits (MRLs), although detectable concentrations of ethylbenzene and xylenes of 0.28 and 1.8 mg/kg, respectively, were detected at 10 feet bgs in one boring (SB-1). However, soil boring SB-1 was drilled in the tank pit, 2 feet shallower than and more than 20 feet away from, the area where elevated concentrations of BTEX were detected during tank closure.

Although, it does not appear that the petroleum release(s) were adequately investigated, ADEQ closed the LUST case files on 23 May 2005. ADEQ's primary rationale for LUST case file closure was the presence of bedrock and lack of groundwater beneath the facility. The LUST facility, however, is generally hydrologically upgradient from the gasoline-impacted wells at the site.


The Johnson Camp mining facility is another potential upgradient source of hydrocarbon contamination, but previous Phase I Environmental Site Assessments conducted by Haley & Aldrich did not reveal evidence of widespread gasoline use at the facility. In fact, most mobile equipment, powered haulage, and beneficiation processes are not using gasoline.

<sup>&</sup>lt;sup>3</sup> Souder, Miller & Associates, 9 April 1996. *Release Confirmation and 14 Day Report Form, Bowlin's The Thing Dairy Queen Travel Center Near Benson, Arizona*.



#### **Corrective Action Requirements**

The Resource Conservation and Recovery Act requires owners and operators to undertake corrective actions in response to releases of petroleum and hazardous waste to the environment. If the source of gasoline is impact from LUSTs, such as an off-site impact from The Thing's LUSTs, then it is the responsibility of the owners and operators of those LUSTs to undertake corrective actions, even if those LUSTs received a prior closure letter from the ADEQ. If the source(s) of impact did not originate from LUSTs, then the applicability of innocent landowner defense under the Comprehensive Environmental Response Compensation and Liability Act should be evaluated.



#### **Enclosures:**

Table I: Summary of Free Product Recovery

Table II: Summary of Detected Analytical Results - Groundwater

Table III: Summary of Chemical Types

Table IV: Summary of BTEX Ratios in Altered Gasoline in Groundwater

Figure 1: Site Plan

Appendix A: Recovered Liquid Disposal Documentation



TABLE I SUMMARY OF FREE PRODUCT RECOVERY EXCELSIOR MINING CORP. GUNNISON COPPER PROJECT DRAGOON, AZ

Location	Date	Time	Depth to Product (feet bgs)	Depth to Water (feet bgs)	Thickness (feet)	Volume <sup>1</sup> (gallons)
	2/5/2015	1718	616.95	618.42	1.47	0.54
	2/11/2015	1450	618.25	618.3	0.05	0.02
CS-10	2/12/2015	0838	617.08	617.1	0.02	0.01
C3-10	2/12/2015	1530	617.03	617.1	0.07	0.03
	2/13/2015	0715	617.29	617.35	0.06	0.02
	2/26/2015	1508	617.2	617.8	0.6	0.22
	2/6/2015	1009	428.98	430.91	1.93	0.71
	2/11/2015	1123	433.15	433.16	0.01	0.00
CS-14	2/12/2015	0838	415.68	415.72	0.04	0.01
CS-14	2/12/2015	1530	409.09	409.1	0.01	0.00
	2/13/2015	0715	402.19	402.2	0.01	0.00
	2/26/2015	1508	No Product Measured	446	0	0.00

#### **NOTES**

1. Assumes corehole diameter is 3 inches and the entire volume of free product is trapped within the corehole. bgs = below ground surface



TABLE II
SUMMARY OF DETECTED ANALYTICAL RESULTS - GROUNDWATER
EXCELSIOR MINING CORP.
GUNNISON COPPER PROJECT
DRAGOON, AZ

		Volatile Organic Compounds (USEPA Test Method 8260B)						Polynuclear Aromatic Hydrocarbons (USEPA Test Method 8310)														
Location	Sample Date	1,2-Dichloroethane	Benzene	Toluene	Ethylbenzene	Xylenes	n-propylbenzene	tert-Butyl Alcohol	1,2,4-Trimethylbenzene	1,3,5-Trimethylbenzene	Anthracene	Acenaphthene	Acenaphthylene	Benzo (g,h,i) perylene	Chrysene	Fluoranthene	Fluorene	Naphthalene	Phenanthrene	Pyrene	1-Methylnaphthalene	2-Methylnaphthalene
CS-10	2/11/2015	<50	7.3	44	30	90	7.1	<25	60	12	12	13	3.5	< 0.050	0.21	<0.050	27	510	86	1.6	690	1000
CS-14	2/11/2015	<5	310	680	110	500	<50	<250	110	<50	4.8	6.6	1.7	0.052	0.067	0.15	16	330	34	0.96	330	460
NSH-007	2/26/2015	<0.50	<0.50	0.59	<0.50	<0.50	<0.50	NA	<0.50	<0.50	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	NA	<0.0050
NSH-009	3/12/2015	<0.50	<0.50	3.93	<0.50	<0.50	<0.50	NA	<0.50	<0.50	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010	NA	<0.010
NSH-015	3/26/2015	0.96	4.56	0.71	<0.10	<0.10	<0.10	NA	<0.10	<0.10	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	<0.0050	0.268	<0.0050	<0.0050	NA	0.0262
NSH-022	04/02/15	<5.0	<5.0	2,080	<5.0	<5.0	<5.0	NA	<5.0	<5.0	<0.0050	<0.0050	<0.0050	0.00614	<0.0050	<0.0050	0.00781	<0.0050	0.00662	<0.0050	NA	0.00776
14011-022	05/04/15	0.36	0.33	NA	0.38	NA	0.35	NA	0.37	0.39	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
NSM-003	2/11/2015	<1	<1	<5	<1	<3	<1	29	<1	<1	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.25	<0.05	<0.05	<0.25	<0.25
Δ.	rizona AWQS	5	5	1000	700	10,000	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE	NE

#### Notes:

**bold** = compound was detected

Concentrations are in micrograms per liter.

AWQS = aquifer water quality standard

EPA = Environmental Protection Agency

NA = sample was not analyzed for the presence of this compound.

NE = standard has not been established for this compound.

USEPA = U.S. Environmental Protection Agency



# TABLE III SUMMARY OF CHEMICAL TYPES EXCELSIOR MINING CORP. GUNNISON COPPER PROJECT DRAGOON, AZ

Detected Compound	Туре	Typical Host Fuel				
1,2-Dichloroethane	Lead Scavenger	Leaded Gasoline				
tert-Butyl Alcohol	Anti-knock/Oxygenate	Unleaded Gasoline				
Benzene						
Toluene						
Ethylbenzene						
Xylenes	Monoaromatic	Gasoline <sup>1</sup>				
n-propylbenzene						
1,2,4-Trimethylbenzene						
1,3,5-Trimethylbenzene						
Anthracene						
Acenaphthene						
Acenaphthylene						
Benzo (g,h,i) perylene						
Chrysene						
Fluoranthene	Polynuclear Aromatic	Gasoline and Diesel <sup>2</sup>				
Fluorene	i diyiladida / ildilladi	Gasonne and Dieser				
Naphthalene						
Phenanthrene						
Pyrene						
1-Methylnaphthalene						
2-Methylnaphthalene						

#### **NOTES**

- 1. Monoaromatics exist, in varying concentrations, in most petroleum fuels. However, their concentrations are most elevated in gasoline.
- 2. Polynuclear Aromatics exist, varying concentrations, in most petroleum fuels. However, their detection at the site is likely to be attributed to gasoline or diesel.

# TABLE IV SUMMARY OF BTEX RATIOS IN ALTERED GASOLINE IN GROUNDWATER EXCELSIOR MINING CORP. GUNNISON COPPER PROJECT DRAGOON, AZ

Compound	We	ells	Ratio in Groundwater <sup>1</sup>			
Compound	CS-10	CS-14	itatio ili Giodildwatei			
B/T	0.46	0.17	0.09 - 21.6			
B/E	2.82	0.24	0.13 - 10.9			
B/X	0.62	0.08	0.01 - 3.5			
T/E	6.18	1.47	0.1 - 9.6			
T/X	1.36	0.49	0.04 - 4.2			
E/X	0.22	0.33	0.08 - 0.55			
B+T/E+X	1.62	0.43	0.11 - 3.4			

#### **NOTES**


1. Kaplan, I. R., Galperin, Y., Lu, S-T. & Lee, R-P. 1997. Forensic environmental geochemistry: Differentiation of fuel types, their sources and release time. Organic Geochemistry 27:289–317. Table 8.

B = benzene

E = ethylbenzene

T = toluene

X = xylenes



#### **APPENDIX A**

**Recovered Liquid Disposal Documentation** 



FREIGHT CHARGES ARE PREPAID ON THIS BILL OF LADING UNLESS MARKED COLLECT.

### STRAIGHT BILL OF LADING

76× ...

*			ORIGINAL — NOT N	EGOTIABLI		5	hipper No	·	
							Carrier No	•	
Page	of <u> </u>	ENGILON	) M&NTAL RESONSE (Name of carrier)	INC.	(SCAC)		Date	· a/	13/15
Cn Collect on Delivery ship	ments, the lette	rs COD" must appear before consignee's	name or as otherwise provided in Item 430, Sec.1.	FROM: Shipper 6	UNNISON C	ppsR	PROTE	σ_	•
	MESI	9 014		Street	EX CGC.5/0	RMI	UNG C	NP	
Street 209	3 S.	57TH AVE		City		State		Ziρ	Code
City PHOEN	ΣLL	State 12	Zip Code <i>25043</i>	24 hr. Emerç	gency Contact Tel. No.	800-	535-5	553	CHEMPLEC.
Route			oost aastaal aasta ka 1900 H Oostaa (1900 H Oostaa) aan aan aan aan aan aan aan aan aa da (1914 H Oostaa) aa a	and the second s	— Cabalor sulvi sukvahurus kuususuususus sura	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Vehic Numb		
No. of Units & Container Type	HM		BASIC DESCRIPTION er Shipping Name, Hazard Class, or NA), Packing Group, per 172.101, 172.2	02, 172.203	TOTAL QUANTITY (Weight, Volume, Gallons, etc.)	(Sub	GHT ject to ection)	RATE	CHARGES (For Carrier Use Only)
1 Om	X	UNI203, GAS	OLINE, 3, PG II		8ga.	8 gar, 50			
				\					
		Wanvel	(ares oil	9. 2	113/15				
Note — (1) Where the rat	e is dependent	S TENDERED: Y on value, shippers are required to state at value of the property, as follows: The	I hereby declare that the contents of this consignment are fully and accurately described	RENU C.O.D. TO: ADDRESS					
agreed or declared value of to be not exceeding	the property is	hereby specifically stated by the shipper	above by the proper shipping name and are classified, packed, marked and labelled/placarded, and are in all respects in proper condition for transport according to applicable international and national	COD Subject to Sect	Amt: \$	oment is to be	C.O.D. FEE: PREPAID C COLLECT C		
release the carrier's liability or declare a value, the carrier's liability shall be limited to the extent provided by such provisions. See NMFC Item 172.  (3) Commodities requiring special or additional care or attention in handling or stowing must be so marked and packaged as to ensure safe transportation. See Section 2(e) of item 360. Bills of Lading. Freight Bills and Statements of Charges and Section 1(a) of the Contract Terms and Conditions for a list of such articles.  Signature			except when box at are			CHARGES  Check box if charges are to be collect			
described abo marked, consi this contract a its usual place	ive in apparent igned, and desti is meaning any of delivery at s	good order, except as noted (contents and ned as indicated above which said carrier (i person or corporation in possession of the p laid destination, if on its route, otherwise to	of the issue of this Bill of Lading, the property condition of contents of packages unknown), the word carrier being understood throughout kopeny under the contract) agrees to carry to defiver to another carrier on the route to said roperty over all or any portion of said route to	shipment. Shipper here	as to each party at eny time interest be subject to all the bill of lading te by certifies that he is familiar with all nd conditions are hereby agreed to b	the lading terms :	and conditions in the	e governing c	lassification and
							( <del></del>	***************************************	

SHIPPER CUNNISON COPPER	LEXCUSION LOND	CARRIER	ENVIRONMENTM	ROSPANSU INC.	<u> </u>
PER		PER	19		
		DATE	2/13/15		<b>U</b>
Permanent post-office address of shipper	A PARTE OF RECOGNIZATION	STYL	E CF26 <b>0/</b> 4	LAREL ASTER @ (800) 621-5808 www.la	belmaster.com



## **RECYCLING MANIFEST / RECEIPT**

135043

### ENVIRONMENTAL

A DIVISION OF MESA OIL, I	VC.			
DATE 2.13.15		SERVICE CALL #	· •	
GENERATOR				
Generator Name Environmental Re	SDOUSE		Contact Paul	Runva
Pickup Address			Phone #	
PICKUP Address		. 13	(5)	10c
City Tempe Mailing Address 2202 W. Medfron		State_ / C	Zip <u>0</u>	<u> </u>
Mailing Address 2202 W. Madton	· C way ste.	108_		
City		State	Zip	
RECYCLING SERVICE	ille kultura kang pimulaga kepada pada pada pada pada pada pada pada	Price / Unit	Quantity	Total
USED OIL REMOVAL		50/dl	5	MC
OILY WATER REMOVAL				**
USED ANTIFREEZE REMOVAL	TO THE NUMBER OF THE PARTY OF T		1 1 1	1.1.
USED OIL FILTER REMOVAL FREIGHT				<u> </u>
SPECIAL INSTRUCTIONS			SALES TAX _	· · · · · · · · · · · · · · · · · · ·
SECULL INCTITION TO THE SECUL	· · · · · · · · · · · · · · · · · · ·		TOTAL DUE	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
			MESA OIL.  \$	
FORM OF	PAYMENT			
	P.#	MC / VISA		
	) BY	P.O.#	经支付股份 化氯化二甲酚 电二十五	11
GENERATORS CERTIFICATION: This material is				
with PCB's or hazardous waste identified in 40 CFR Part	described to the best of fily are 261. Used oil filters meet the	exclusion reau	irements of 40	CFR Part
261.4. I acknowledge the accuracy of the total due on thi	s receipt. If to be charged on	account I unde	erstand that an	invoice will
follow with terms of NET 30 DAYS.	Ade		4 10	سير ا
Dose Sory	<u> </u>		1.13	15
Printed / Typed Name Sign	ature		Date	
TRANSPORTER. S	STORER AND RECYCLE	<b>z</b> B		(Carlotte - Carlotte -
MESA OIL, INC PLANT MESA OIL, INC PLANT				anno do come de describo de come
Belen, NM Phoenix, AZ	Mailing Address:			
EPA# NM 0000096024 EPA# AZR000033381 TEXAS TNRCC ID# A85467	Mesa Oil, Inc.	ouwwia a sa	IN CASE O	
	7239 Bradburn Blvd	li A.	PILL CONTA	
MESA OIL, INC PLANT Golden, CO	Denver, CO 80030	28 6	iesa oil, in	
EPA# COD 982581993	(303) 426-4777	1.	-800-USED-	OIL
TRANSPORTER ACKNOWLEDGMENT OF RECEIPT OF	MATERIALS:	E Commonweal		
I certify materials have been tested and are below 1,000 F	PPM halogens.	D.O.T. REQUIR U	EMENT - MAXIMUM LO SED PETROLEUM OIL I	AD 7000 GALLONS N.O.S.
Manyal (ans	). /-//		2.12	15
	ature/		Date	
TREATMENT FACILITY OPERATOR:				
The described materials were handled by me, the treatme	nt facility named above, and w	were accepted		
Printed / Typed Name Cian	Atura 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		STREET DV STEET	